




The bottom surface and the back of the amplifier are black lacquered on all models.



## Finishes

**AT440N**  Matt black

**AT440N**  Silver lacquered

**AT440N**  Gloss white lacquered RAL 9016



## Stereo - IcePower® based

<b>Power W RMS</b> 2 ch 4 Ω - 8 Ω	120 x 2 - 70 x 2
<b>Power W RMS</b> bridge 4 Ω - 8 Ω	440 x 1 - 240 x 1
<b>Input</b>	2 x RCA Unbalanced inputs
<b>Output connection</b>	Terminal blocks
<b>Max power consumption (W)</b>	520
<b>Distortion (THD+N)</b>	THD+N = 0.002% @ 1W (8Ω, 1kHz, 2 ch-bridge mode)
<b>Intermodulation distortion</b>	0.0009%, 10W, 4Ω, 18.5kHz/1kHz
<b>Frequency response (Hz)</b>	20 - 20K ± 0,15 dB
<b>Signal to noise ratio (dBA)</b>	98
<b>Input sensitivity (V RMS)</b>	80 mV - 3,0 V
<b>Input impedance (Ω)</b>	47 K
<b>Power supply</b>	AC 230 V, 50 Hz
<b>Power-on modes</b>	Power switch
<b>Protection</b>	Thermal, Overcurrent
<b>Dimensions</b> H x W x D (cm)	6,0 x 10,0 x 25,5
<b>Weight (Kg)</b>	1,40

## Accessories

### Code: HKL044



2U Rack 19"  
frame supporting  
4 amplifier  
modules



Dimensions  
H x W x D (cm)  
8,8 x 48,3 x 0,4

Weight (Kg) 0,25

### Code: HNL010



Blanking panel  
for HKL044



Dimensions  
H x W x D (cm)  
8,8 x 10,0 x 1,0

Weight (Kg) 0,30



This accessory  
is included in  
the package of  
AT440 and AW440  
amplifiers.



Installation brackets

Dimensions H x W x D (cm)  
1,3 x 1,3 x 9,8

Weight (Kg) 0,10



Finishes



Specifiche  
tecniche



## Specifications

Specifiche  
Caractéristiques  
Spezifikationen  
Link: [www.garvan.it/gat](http://www.garvan.it/gat)

