



The bottom surface and the back of the amplifier are black lacquered on all models.



Finishes

AT440N  Matt black

AT440N  Silver lacquered

AT440N  Gloss white lacquered
RAL 9016



Stereo - IcePower® based

Power W RMS 2 ch 4 Ω - 8 Ω	120 x 2 - 70 x 2
Power W RMS bridge 4 Ω - 8 Ω	440 x 1 - 240 x 1
Input	2 x RCA Unbalanced inputs
Output connection	Terminal blocks
Max power consumption (W)	520
Distortion (THD+N)	THD+N = 0.002% @ 1W (8Ω, 1kHz, 2 ch-bridge mode)
Intermodulation distortion	0.0009%, 10W, 4Ω, 18.5kHz/1kHz
Frequency response (Hz)	20 - 20K ± 0,15 dB
Signal to noise ratio (dBA)	98
Input sensitivity (V RMS)	80 mV - 3,0 V
Input impedance (Ω)	47 K
Power supply	AC 230 V, 50 Hz
Power-on modes	Power switch
Protection	Thermal, Overcurrent
Dimensions H x W x D (cm)	6,0 x 10,0 x 25,5
Weight (Kg)	1,40

Accessories

Code: HKL044



2U Rack 19" frame supporting 4 amplifier modules



Dimensions
H x W x D (cm)
8,8 x 48,3 x 0,4

Weight (Kg) 0,25

Code: HNL010



Blanking panel for HKL044



Dimensions
H x W x D (cm)
8,8 x 10,0 x 1,0

Weight (Kg) 0,30



This accessory is included in the package of AT440 and AW440 amplifiers.



Installation brackets

Dimensions H x W x D (cm)
1,3 x 1,3 x 9,8

Weight (Kg) 0,10



Finishes



Specifiche tecniche



Specifications

Specifiche
Caractéristiques
Spezifikationen

Link: www.garvan.it/gat

